



3B CONCRETE PLACEMENT PLAN - MAIN LEVEL  
SCALE: 3/32" = 1'-0"

- PLAN NOTES**
- FURNISH & INSTALL NEW INTEGRAL CONCRETE SLAB PER SPECIFICATION SECTION 033105. MATCH EXISTING ADJACENT SLAB LEVEL TO PROVIDE A SMOOTH/FLUSH TRANSITION. COORDINATE EXACT LOCATIONS AND EXTENTS OF WORK FOR EACH AREA WITH PLUMBING DRAWINGS.
  - FURNISH & INSTALL NEW CONCRETE SLAB. MATCH EXISTING SLOPES OF ADJACENT EDGES. DEPRESS SLAB, SET TO MATCH ADJACENT SLAB EDGE, TO ACCOMMODATE TILE FLOOR FINISH & PROVIDE A SMOOTH/FLUSH FINISHED SURFACE W/ ADJACENT FLOOR. FURNISH & INSTALL NEW FLOOR FINISH TO MATCH EXISTING ADJACENT. COORDINATE EXACT LOCATIONS AND EXTENTS OF WORK FOR EACH AREA WITH ARCHITECTURAL & PLUMBING DRAWINGS.

- GENERAL NOTES**
- ALL NEW SLABS SHALL BE A MINIMUM OF 4" THICK 3,000 PSI CONCRETE OVER A MINIMUM OF 4" THICK OF POROUS FILL PER SPECIFICATION SECTIONS 030180, 033105 & 033110.
  - COORDINATE EXACT LOCATIONS OF ALL NEW INTERIOR FLOOR SLABS W/ SHEETS A01.2, A1.1, A4.1, A4.2 & PLUMBING SHEETS.
  - ALL NEW SLABS SHALL RECEIVE CONTROL JOINTS @ MAX. 12'-0" O.C. EACH WAY. NEW SLABS POURED ADJACENT TO EXISTING SLABS SHALL HAVE JOINT LOCATIONS ALIGN W/ EXISTING ADJACENT LOCATIONS.
  - ALL NEW INTERIOR SLABS POURED AGAINST WALLS OR COLUMNS SHALL HAVE A LAYER OF 30# BUILDING FELT FROM BOT. OF POUR UP TO MIN. 6" ABOVE TOP OF SLAB AS BOND BREAK. FELT TO BE TRIMMED DOWN TO TOP OF SLAB AFTER PROPER CURING HAS OCCURRED.
  - ALL NEW SLABS POURED AGAINST EXISTING SLABS SHALL BE DOWELED TOGETHER PER ASD-69.
  - SLABS SHALL BE DEPRESSED 3/8" BELOW MAIN FINISHED FLOOR LEVEL IF RECEIVING A TILE FINISH.

**LEGEND**

	INDICATES AREA OF NEW SLAB.
	INDICATES AREA OF NEW DEPRESSED SLAB

NO.	DATE	DESCRIPTION